

Correspondence with previous models	ino-800	ino-810	ino-820	ino-840	WT7000	WT7100	XT5-800	XT5-Pro	XP-6600	WT-7600	XT7-800	XT7-Pro	XP-6700
Comparison note with new ino900, Compact 9000 and Ultra 9000 Series	The new 900 series offers 2 front USB and 2 rear USB, VIA processor with Wide Screen resolution				The new 9000 Compact series does not offer anymore the LPT1 and Com2 ports. It is available the optional USB to Parallel adapter. New VESA mounting LCD available.				The new 9000 Ultra series has LPT1 and COM2 with an option, in alternative it is available the optional USB to Parallel adapter.				
	New Ino 900 Series				New Compact 9000 Series				New Ultra 9000 Series				
Technical Specifications	XT900-I	WT910-I	XT920-I	XP940-I	WT9000-C	WT9100-C	XT9000-C	XT9200-C	XP9400-C	WT9100-U	XT9000-U	XT9200-U	XP9400-U
Processor/ Chipset	VIA Eden ULV 500MHz / CN700				VIA C7 1GHz / VIA VX800				VIA Eden ULV 1.6GHz / VIA VX800				
Power supply	External 100/240VAC 50/60Hz, 12V 2A - 24W				External 100/240VAC 50/60Hz, 12VDC / 4A max				External 100/240VAC 50/60Hz, 12VDC / 4A max				
Power consumption: on / stand-by	9W / 1.9W standard, 11W /1.9W with built-in wireless				15W / 2.4W standard, 17W /2.4W with built-in wireless				16W / 2.4W standard, 18W /2.4W with built-in wireless				
Device dimension, weight	15,6(H) x 12,2(P) x 3,6(L) cm, 0,640 Kg				23,0(H) x 21,0(P) x 4,4(L) cm, 1,4Kg				23,0(H) x 21,0(P) x 5,7(L) cm, 1,7Kg				
Packaging dimension, weight	22,1(H) x 23,2(P) x 8,5(L) cm, 1,410 Kg				36,5(H) x 31,0(P) x 8,5(L) cm, 2,6Kg				36,5(H) x 31,0(P) x 8,5(L) cm, 2,8Kg				
Device certifications / Power Supply certification	CE, FCC Class B / CE, FCC Class B, GS TUV,UL				CE, FCC Class B / CE, FCC Class B, GS TUV,UL				CE, FCC Class B / CE, FCC Class B, GS TUV,UL				
Temperature range / humidity	0° ÷ 35° / 20% ÷ 80%				0° ÷ 35° / 20% ÷ 80%				0° ÷ 35° / 20% ÷ 80%				
Security lock	kensington				kensington				kensington				
Operating System	ThinOX V8	CE 6.0R2	ThinOX V8	XPe SP3	CE 6.0R2	CE 6.0R2	ThinOX V8	ThinOX V8	XPe SP3	CE 6.0R2	ThinOX V8	ThinOX V8	XPe SP3
RAM Memory / Flash memory	512MB / 256MB	256MB / 128MB	512MB / 256MB	512MB / 1GB	256MB / 128MB	256MB / 128MB	512MB / 256MB	512MB / 512MB	1GB / 1GB	256MB / 128MB	512MB / 256MB	512MB / 512MB	1GB / 1GB
Display resolution with DDC, 4:3, 16:10 WIDE ratio	1920 x 1440				1920 x 1440				1920 x 1440				
Colors	from 256 to 16,8 Million included				from 256 to 16,8 Million included				from 256 to 16,8 Million included				
Optical PS/2 mouse													
Peripherals													
USB external ports	2 USB 2.0 front + 2 USB 2.0 rear				2 USB 2.0 front + 2 USB 2.0 rear				2 USB 2.0 front + 2 USB 2.0 rear				
USB internal ports	1 USB 2.0 port reserved for optional built-in wireless				2 USB 2.0 reserved for optional built-in wireless and Smart Card reader				2 USB 2.0 reserved for optional built-in wireless and Smart Card reader				
LAN Ethernet	10/100/1000 BaseT Ethernet RJ45				10/100/1000 BaseT Ethernet RJ45				10/100/1000 BaseT Ethernet RJ45				
Monitor	1 SVGA (DB15) port				1 DVI-I port with DVI to VGA included – optional dual monitor DVI / VGA adapter				1 DB15 VGA/SVGA port, 1 DVI port				
PS/2 Mouse and Keyboard	1 PS/2 port, PS/2 mouse and keyboard adapter included				1 PS/2 port, PS/2 mouse and keyboard adapter included				1 PS/2 port, PS/2 mouse and keyboard adapter included				
Serial port	--				1 porta COM1 di serie				1 porta COM1 di serie + 1 porta COM2 opzionale				
Parallel Port	With optional USB to Parallel cable adapter				With optional USB to Parallel cable adapter				With optional USB to Parallel cable adapter				
Audio In MIC / Audio Out Headphones	1 x 1/8 inch jack / 1 x 1/8 inch jack				1 x 1/8 inch jack / 1 x 1/8 inch jack				1 x 1/8 inch jack / 1 x 1/8 inch jack				
Expansion slot	--				--				1 PCI slot (used for LPT1+COM2 optional card)				
Built-in 802.11b/g Wireless	Factory option with external antenna				Factory option with built-in antenna				Factory option with built-in antenna				
Built-in speaker	Built-in speaker 1 W				Built-in speaker 1 W				Built-in speaker 1 W				
Protocols and resident clients													
TCP/IP, DNS, DHCP, FTP, SNMP MIB II	•				•				•				
802.1X Ethernet EAP/PEAP MSCHAPV2 Authentication	•				•				•				
RDP Client	RDP 6.0*	RDP 6.0	RDP 6.0*	RDP 7.0	RDP 6.0	RDP 6.0	RDP 6.0*	RDP 6.0*	RDP 7.0	RDP 6.0	RDP 6.0*	RDP 6.0*	RDP 7.0
Citrix ICA, PN Agent, Citrix XenDesktop Clients	ICA 11.1	ICA 10.0	ICA 11.1	ICA 11.2	ICA 10.0	ICA 10.0	ICA 11.1	ICA 11.1	ICA 11.2	ICA 10.0	ICA 11.1	ICA 11.1	ICA 11.2
Citrix HDX - MediaStream Server Rendered Media	•				•				•				
Citrix HDX - MediaStream Client Rendered Media	•				•				•				
Citrix HDX Plug & Play (USB redirection) support	•				•				•				
VMware View Client	4.0/RDP	3.1/RDP	4.0/RDP	4.0/RDP	3.1/RDP	3.1/RDP	4.0/RDP/PCoIP	4.0/RDP/PCoIP	4.0/RDP/PCoIP	3.1/RDP	4.0/RDP/PCoIP	4.0/RDP/PCoIP	4.0/RDP/PCoIP
VMware View MMR support	•				•				•				
USB re-direction client VMware View	•				•				•				
USB re-direction client Praim (TCe Virtual Desktop Agent)	•				•				•				
Ericom PowerTerm WebConnect Client	•				•				•				
Leostream Client	•				•				•				
Provision Networks VAS (Quest software) Client	•				•				•				
Browser	Firefox 3.0.1	IE 6.0 – CE 6.0	Firefox 3.0.1	IE 7.0 – WIN32	IE 6.0 – CE 6.0	IE 6.0 – CE 6.0	Firefox 3.0.1	Firefox 3.0.1	IE 7.0 – WIN32	IE 6.0 – CE 6.0	Firefox 3.0.1	Firefox 3.0.1	IE 7.0 – WIN32
Pram TN5250E / 3270 Video e Printer Emulator	•				•				•				
Pram VT/ASCII Emulator	•				•				•				
Local PDF Viewer	•				Acrobat PDF 7.0				Acrobat PDF 7.0				
MS Office Viewers	•				•				•				
Media Player, Wordpad	•				•				•				
E-mail client	•				Outlook express				Thunderbird 2.0		Outlook express		
JVM	•				•				SUN 1.5		SUN 1.5		
Flash Player	•				•				Adobe Flash		Adobe Flash		
Open Office	•				•				OpenOffice 2.3		OpenOffice 2.3		
Skype local voip Client	•				•				•				
NX Nomachine Client	•				•				•				
X11 nativo Client	•				•				•				
Propalms TSE Client	•				•				•				
VNC Client	•				•				•				
Shell script session	•				•				•				
CUPS printing	•				•				•				
Cisco VPN Client	•				•				•				
LPD/LPR and RAW	•				•				•				
User Disk partition	•				approx 250MB				50MB		approx 250MB		
USB re-direction client Praim (TCe Virtual Desktop Agent)	•				•				•				
Supported Operating Systems – Administration													
Citrix Metaframe 1.7, 1.8, XP, PS Server 4, 4.5	•				•				•				
Citrix XenApp 5.0, Citrix XenDesktop 3.x, 4,0	•				•				•				
VMware View 3,1, 4,0	•				•				•				
Microsoft Windows 2000/2003/2008 Terminal Server	•				•				•				
Unix/Linux/AIX	•				•				•				
IBM AS/400, IBM S/390	•				•				•				
Central Remote administration via Praim ThinMan	•				•				•				
ThinMan Enterprise profile manager support	•				•				•				
Remoto fw Update / VNC shadowing / Wake On LAN	•				•				•				
Security password and screen saver password	•				•				•				
Options													
External USB WiFi USB 802.11b/g dongle	80AC00031				80AC00031				80AC00031				
Built-in wireless 802.11b/g with internal antenna	80AC00060				80AC00061				80AC00061				
Built-in smart card reader	--				80AC00065				80AC00065				
PCI adapter with LPT1 + COM2	--				--				80AC00070				
Dual monitor adapter from DVI-I to DVI and VGA	--				80EC00019				--				
USB to Parallel cable adapter	80EC00012				80EC00012				80EC00012				
Flash disk expansion	--	--	--	2GB, 4GB	--	--	--	--	2GB, 4GB	--	--	--	2GB, 4GB
RAM memory DDR2 expansion	1GB	512MB, 1GB	1GB	1GB	512MB,1GB,2GB	512MB,1GB,2GB	1GB,2GB	1GB,2GB	1GB,2GB	512MB,1GB,2GB	1GB,2GB	1GB,2GB	1GB,2GB
105 keys PS/2 keyboard with PC standard layout	89T1100x1				89T1100x1				89T1100x1				
105 keys PS/2 keyboard with PC/5250 double layout	89T1100x2				89T1100x2				89T1100x2				
LCD VESA mounting KIT with VGA cable	80EC00017				80EC00018				--				
Pram Media streaming codecs Add-On software license	76AC00006	76AC00006		76AC00006		76AC00006		76AC00006		76AC00006	76AC00006		76AC00006