


Praim Thin Client *All-In-One Series*



www.praim.com



The new series All-In-One combines all the technology of Praim with the quality of the LED monitor of Samsung.

- The ideal workstation for enterprise environments and wherever a stylish and compact solution is needed
- Ideal workstation to access any centralized infrastructure, integrates support versus Citrix XenDesktop and VMware View and Microsoft
- The quality of the monitor Samsung with LED technology
- Adjustable height and adjustable pivot
- Very low power consumption, is a Green solution, only 13W
- High Reliability and Easy Remote Management with ThinMan Console, provide a lower Total Cost of Ownership (TCO) than a traditional PC or laptop.
- Simple and Secure access to company applications, without the risk of Virus infection
- Enhanced IBM AS/400 Display and Printer emulation.

Technical Specifications	XT9050-TC180	XT9200-TC180
P/N	80X9050TC180	80X9200TC180
Processor/ Chipset	Intel Atom N270 1.6GHz / Intel 945GSE + ICH7-M	
Power supply	Integrated 100/240VAC 50/60Hz	
Power consumption: active / stand-by	Max 45 W, Tipycal 30 W / Less than 2.7 W	
Device dim. with stand, weight / Packaging dim. , weight	443.4(L) x 334.8(H) x 197.0(P) mm, 5.1Kg / 483.0(L) x 400.0(H) x 190.0(P), 6.25Kg	
Wall mount	VESA 100x100	
Device certifications	CE, FCC Class B, GS, TUV, UL, Energy Star 5.0	
Temperature range / humidity	0° ÷ 35° / 20% ÷ 80%	
Security lock	Kensington	
Operating System	ThinOX V8	
RAM memory / Flash memory	1GB / 1GB	
Panel		
Size – Viewable size	18,5" - 18,5"	
Stand	Swivel / Pivot / Height Adjustable	
Panel type	a-Si TFT active matrix	
Aspect ration	16:9	
Pixel pitch (H x V)	0.300 x 0.300 mm	
Brightness (typical)	250 cd/sq.m	
Contrast (typical)	1000:1	
Viewing angle (H - V)	170/160° (CR≥10) - 178/178° (CR≥5)	
Frequency		
Horizontal - Vertical	31~60 kHz - 56~75 Hz	
Maximum resolution (H x V)	1366 x 768	
Frequency	85.5 MHz	
Colors supported	16.7 Millions	
Peripherals		
USB ports - Parallel - Serial	4 x USB 2.0 - 1 x Parallel (25 pin D-SUB) - 1 x RS232-C (9 pin D-SUB)	
LAN Ethernet	1 x Marvell 88E8055 Gigabit LAN	
Monitor In/Out	RGB IN (15 pin D-SUB)/Video Out (15 pin D-SUB)	
Audio In / Audio In MIC / Audio Out Headphones	1 x 1/8 inch jack / 1 x 1/8 inch jack / 1 x 1/8 inch jack	
Built-in speakers	Built-in speakers 1 W	
Protocols and resident client		
TCP/IP, DNS, DHCP, FTP, SNMP MIB II	.	
802.1X Ethernet EAP/PEAP MSCHAPV2	.	
Cisco VPN Client	.	
Client RDP	7.0	
Client VMware View 5.0	RDP/PCoIP	
Citrix ICA / PN Agent / Receiver	ICA 12	
Virtual Bridges VERDE 5.5	SPICE	
Client Ericom PowerTerm WebConnect	.	
Client Leostream / Client Provision Networks VAS	.	
Browser	Firefox 3.0.1	
Local PDF Viewer	Acrobat 7	
Praim TN525E / 3270 Video/Printer emulator	.	
Praim VT/ASCII emulator	.	
E-mail client	Thunderbird 2.0	
JVM	SUN 1.6	
Open Office	Open Office 3.3	
Flash Player	Adobe 11	
Local client voip Skype	.	
NX Nomachine client	.	
X11 client	.	
Propalms TSE client	.	
VNC client	.	
Shell script session	.	
CUPS printing	.	
LPD/LPR and RAW	.	
User disk partition	50MB	
Praim USB re-direction	☐	
Supported operating systems		
Citrix Metaframe 1.7, 1.8, XP, PS Server 4, 4.5	.	
Citrix XenApp 6.0, Citrix XenDesktop 5.0	.	
Microsoft Windows 2000/2003/2008 TS	.	
Unix/Linux/AIX, NX NoMachine Server	.	
IBM AS/400, IBM S/390	.	
Administration		
Remote management via Praim ThinMan	Freeware, Enterprise, Platinum	
Upgrade FW /VNC shadow/ WakeOnLAN	.	
Screen saver with password	.	
Options	Codice	
External USB WiFi USB 802.11b/g dongle	80AC00031	
Praim Media streaming codecs Add-On	76AC00006	
Warranty		
3 year ex-factory, advanced replacement not available.		
Note: · Available ◊ Installable from user based on available free disk space		
Praim Srl - info@praim.com - www.praim.com - T. +39 0461 420517 - F. +39 0461 420581 - Via Ezio Maccani 191, 38121 TRENTO - ITALY		
All names and trademarks contained in this document, are property of their respective owners. The information in this document is property of Praim SRL.		