



Domino NEXT

The new All-In-One with integrated webcam to support collaborative work

All the advantages of a unique solution

Domino NEXT guarantees all the performances and advantages of a Thin Client, in minimal space. An All-In-One workstation that allows a unique workspace organization, saving time and installation costs. All the power of the Intel Celeron J4105 processor, to take full advantage of all its features and versatility of use.



Versatility up to 3 monitors and 4K support

Domino NEXT is an elegant and compact workstation. The 24" Full HD monitor has an essential line that, together with the possibility to connect up to two other monitors up to 4K, guarantees a unique style.

The multitasking All-In-One

The 6 USB ports (2 USB 3.0 ports and 4 USB 2.0 ports), a USB type C port, vertical adjustment, monitor pivot rotation and integrated webcam make Domino NEXT a fully connected workstation ready to support you to work in collaborating with your team.

Model	D9254	D9219	D9221
Type	Thin Client	Thin Client	Thin Client
Processor / Chipset	Intel Celeron J4105 (Quad Core 1.5GHz, up to 2.5GHz), Fanless		
Power supply	External 100~240V (50/60Hz) 65 W		
Power consumption: on / stand-by	25 W / 1.24 W		
Device dimensions / weight	553.4 (W) x 240 (D) x 382.7 (H) mm / 6.2 Kg (with stand)		
Packaging dimensions / weight	634 (W) x 174 (D) x 462 (H) / 8.6 Kg		
Certifications	CB, FCC-B, UL, CE, RoHS, REACH, TÜV type, TÜV-ERGO, EPA Energy Star, EPEAT BRONZE, ErP		
Operational temperature / humidity	10°C ÷ 40°C / 20% ÷ 80% non-condensing		
Security lock	Kensington lock		
Maximum display resolution (integrated)	1920x1080 Full HD		
Maximum display resolution (external)	Up to 2 displays: 3840x2160 @60Hz (via Display Port 1.2), 3840x2160 @60Hz (via USB Type-C)		
Built-in speaker	2ch Stereo x 3W		
Webcam	Integrated (pop-up type) Full HD with microphone (no webcam app provided)		
TPM Module	Trusted Platform Module 2.0 (standard)		
Operating system	ThinOX v.12	WIN 10 IoT 2019 LTSC	WIN 10 IoT 2021 LTSC
RAM memory / Flash memory	8GB/128GB		



Integrated Monitor	D9254	D9219	D9221
Display ratio		16:9	
Display data control		Intel UHD Graphics 600	
Integrated monitor		24" IPS Display	
Pixel pitch		0.2745 x 0.2745 (mm)	
Glass treatment		Anti glare, 3H	
Contrast ratio		1000:1 (Typ)	
Viewing angle LR / UD		178/178(CR≥ 10)	
Luminance		250 cd/m2 (Typ) / 200 cd/m2 (Min)	
Response time		5ms (High)	
Backlight		IPS Display	
Input / Output			
USB ports		4 x USB3.1 (rear) + 1 x USB Type C (rear) + 2 x USB2.0 (lateral)	
Display-only ports		1 x DP (output) + 1 x HDMI (input)	
Audio - Mic In		1 x 3.5mm audio-mic combo jack (CTIA Type)	
Audio - Line Out		1 x 3.5mm audio-mic combo jack (CTIA Type)	
Networking			
Ethernet		RJ45 10/100/1000 Base T Gigabit Ethernet	
Wireless		Dual Band 802.11 a/b/g/n/ac 2x2" (BlueTooth 5.0 Combo, Internal Antenna)	
WiFi model		Intel AC 9560	
Mounting			
Monitor Stand, Height Adjustable with Pivot 90° Swivel		✓	
Packaging included			
Power cord		✓	
USB optical mouse		Optional	
Firmware			
Version	ThinOX	WIN 10 IoT 2019 LTSC	WIN 10 IoT 2021 LTSC
Architecture	x86	x86	x86
System type	64 bit	64 bit	64 bit
Version	12	4	4
Size	~ 4 GB	~20 GB	~20 GB
Quick boot	-	✓	✓
UEFI support	✓	✓	✓
Supported protocols			
TCP/IP, DNS, DHCP	✓	✓	✓
SSH	✓	-	-
802.1X Ethernet EAP/PEAP MSCHAPV2	✓	✓	✓

Supported Infrastructures			
Citrix Workspace App	HDX, H.264, optimized Microsoft Teams, optimized Zoom, HDX Real-Time	HDX, H.264, H.265, optimized Microsoft Teams, optimized Zoom, HDX Real-Time	HDX, H.264, H.265, optimized Microsoft Teams, optimized Zoom, HDX Real-Time
VMware Horizon	Blast, RDP, PCoIP, optimized Microsoft Teams, optimized Zoom	Blast, RDP, PCoIP, optimized Microsoft Teams, optimized Zoom	Blast, RDP, PCoIP, optimized Microsoft Teams, optimized Zoom
Microsoft Remote Desktop Services	Free RDP	Microsoft (MSTSC Client)	Microsoft (MSTSC Client)
Azure Virtual Desktop/Microsoft 365	-	Microsoft (MSRDC Client)	Microsoft (MSRDC Client)
Parallels Remote Application Server	Parallels RAS, standard RDP	Parallels RAS, standard RDP	Parallels RAS, standard RDP
UDS Enterprise	UDS Client	UDS Client	UDS Client
Installed Applications			
Local Browser	✓	✓	✓
Local PDF viewer	✓	-	-
JVM / JRE	✓	-	-
Flash player	✓	✓	✓
Shell Script	Bash	Power Shell	Power Shell
IBM i Access Client	✓	✓	-
Smart card support	✓	✓	-
Praim Agile	-	✓	✓
Putty VT/ASCII emulation	✓	✓	-
Printing			
Printer support	✓	✓	✓
VPN			
Barracuda, Fortinet, IKE (Cisco), OpenConnect VPN Client (Cisco Anyconnect), OpenVPN, SonicWall NetExtender	✓	✓	✓
Add on			
SafeNet Etoken Pro	✓	-	-
Imprivata One Sign No Click Access agent	✓	✓	✓
Warranty			
Hw warranty - On Center Warranty	3 years		
Hw warranty extension	Up to 5 years		